A multim de digital m dem

Patent number: EP0806852

Publication date: 1997-11-12

Inventor: CHEN WALTER Y (US); FRANTZ GENE A (US); WU SONG S (US); LU XIAOLIN (US); RILEY TERENCE J (US); SHAVER DONALD P (US); TIMM WILLIAM C (US); GARCIA DOMINGO G (US); MANNERING DENNIS G (US); POLLEY MICHAEL O (US)

Applicant: TEXAS INSTRUMENTS INC (US)

Classification:

- international: H04L5/14; H04L1/12; H04L25/03; H04L27/26

- european: H04L1/00A1M, H04L1/00B2, H04L25/03, H04L27/26M5A, H04L5/14R, H04L1/00A5, H04L25/03B9, H04L25/49M1Q, H04L27/26M5, H04M11/06, H04M11/06B

Application number: EP19970303071 19970506

Priority number(s): CA19972217073 19971001; US19960645020 19960509; US19960667267 19960620

Also published as:

US6055268 (A1)
EP0806852 (A3)
CA2217073 (A1)

Cited documents:

WO9419877
EP0621708
US5371734
US5475735
EP0180066
more >>

Abstract of **EP0806852**

A modem that operates selectively in the voice-band frequency band and at higher frequency bands is provided. This modem supports multiple line codes, like DMT and CAP.
The modem uses a Digital Signal Processor (DSP), so that different existing ADSL line codes, such as Discrete MultiTone (DMT) and Carrierless AM/PM (CAP), can be implemented on the same hardware platform. The modem negotiates in real-time, for a desired line transmission rate to accommodate line condition and service-cost requirement.
The line code and rate negotiation process may be implemented at the beginning of each communication session through the exchange of tones between the modems. A four-step MDSL modem initialization process is provided for line code and rate compatibility.
A new synchronization startup procedure for CAP based MDSL modems is provided. The handshake protocol and receiver algorithm allow reliable modem synchronization over severely amplitude distorted channels such as standard telephone twisted-pair wire. the algorithm makes use of a short length sequence to train a synchronizing equalizer at the receiver. After training to this sequence, a matched filter or correlator is used to detect the inverted sync sequence. The detection of the inverted sequence signals the start of the normal reference training o the CAP demodulation equalizers.



FIG. 1a

The MDSL line connection manag ment pr c ss provid s a simpl , efficient, and flexible interface to mange the line connection between MDSL-C (MDSL in Central Office site) and MDSL-R (MDSL in resident site) in the telecommunication Wide Area Networking environment. An internal state machine in an MDSL modem records and monitors the line status and notifies the state change to the other MDSL and also the host processor. The protocol used for exchanging line connection management messages is a simplified Link Control Protocol (LCP) for MDSL.
